



# tres900

The tres900 reader is value engineered to meet your most demanding applications for asset and personal monitoring, vehicle ID and supply chain management.

Integrated antenna design means simple installation and functionality in a single, low profile design, tres900 is environmentally sealed allowed for indoor and outdoor installations with a UV resistant housing.

**tres900 is a Long Range UHF Reader frequency hopping at 902 to 928 MHz**

**Read Ranges between 15 to 30 feet, depending on installation**

**Reads EPC Class 1 Gen2 tags and outputs 26 bit Wiegand and RS232**

**RF Power Range of 20 to 30 dBm, Software Adjustable**

**Tag ID modes configurable to either Timing or Trigger Mode**

**Supplied 3 Amp power supply, reader takes 1.5 Amps**

**FCC Part 15 and CE certified with an IP65 rating**



tresfsolutions.com  
217 Fulton Court, PeachTree City GA  
30269

888-574-8737

## Hang Tags



tres-900-HT600-G Hang Tag  
tres Generic Logo Graphics  
6.0x2.125x0.04in

tres-900-HT600-W Hang Tag  
Generic White, No Graphics  
6.0x2.125x0.04in

tres-900-HT600-GN Hang Tag  
tres Generic Logo Graphics  
No Number  
6.0x2.125x0.04in.

## Custom Hang Tags

tres-900-HT350-C Hangtag  
Custom Graphics  
3.50x3.50x0.003in

tres900-HT600-C Hangtag  
Custom Graphics  
6.0x2.125x0.04in

HT350-C



HT600



## Windshield Tags



tres-900-WS421-C  
Windshield Stickers Custom  
4.0x1.0in

tres-900-WS421-Oval  
Windshield Custom  
4.5x2.5in

tres-900-Viper  
Clear/Covert, Windshield Sticker  
4.75x0.625in

tres-900-WS421-G  
tres Logo labeled Windshield Sticker  
4.0x4.0in

tres-900-WS421-W  
Plain White, Windshield Sticker  
4.0x1.0in.

WS421-OVAL



WS421-W



## ISOM



tres-900-ISO-G2PRX ISO  
Combo Card, Multi-Technology  
900MHz/125KHz

tres-900-ISO-G2SMRT ISO  
Combo Card, Multi-Technology  
900MHz/13.4MHz

tres-900-ISOM ISO  
Graphics Gen2 PVC Card

## Metal Tag

Stealth



tres-900-Stealth  
ABS Encased Metal Mount Tag  
5.12x1.65x0.42in w/Tabs

## Headlamp Tag

Viper



tres-900-Viper  
Head Lamp Tag  
4.75x0.625



All tags get between  
15' to 25' read range  
depending on installation

