



tres2prox



Engineering Innovation

Our tres2prox card provides single secure credential for less management and more convenience. This durable PVC card is suitable for everyday or harsher environment uses. Combined with the ideal surface for single or double sided high quality printed graphics, this ISO card is sized for uniform, consistent and long lasting quality performance. Combined technology choices: AVI, proximity, smartchip magstripe, etc.

125kHz: Specifications:

Compliant with ISO and ABA standards
Standard 26-bit Wiegand Format Protocol
125 kHz, single read per presentation
Portrait or landscape punch capability
White color, printable graphics quality
Optional programmable ABA magstripe
Read range: 3" - 18"
Dimensions: 3.375"x2.125"x0.033"

900MHz Specifications:

EPC G2 protocol, Impinj Monza 4QT inlay
ISO PVC compliant thickness for badges
Portrait or landscape punch capability
White color, 2-side printable graphics quality
Standard 26-bit Wiegand format protocol
Standard ASCII serial data format protocol
Read range: 20 to 30 feet
Dimensions: 3.375"x2.125"x0.033"





tres2smart



Smartcard Technology

Our tres2prox card provides single secure credential for less management and more convenience. This durable PVC card is suitable for everyday or harsher environment uses. Combined with the ideal surface for single or double sided high quality printed graphics, this ISO card is sized for uniform, consistent and long lasting quality performance. Combined technology choices: AVI, proximity, smartchip magstripe, etc.

125kHz: Specifications:

Compliant with ISO and ABA standards
Standard 26-bit Wiegand Format Protocol
125 kHz, single read per presentation
Portrait or landscape punch capability
White color, printable graphics quality
Optional programmable ABA magstripe
Read range: 3" -18"
Dimensions: 3.375"x2.125"x0.033"

13.56 MHz: Specifications:

ISO PVC compliant thickness for badging
White color, 2-sided printable graphics quality
Open architecture protocol: ISO-14443
Smart credential 1k or 4k bits of storage
Optional programmable ABA standard magstripe
Used for access, transit, vending, cafeteria, etc.
Read range: 2"-3"
Dimensions: 3.375"x2.125"x0.033"

